



F-150 Platinum SuperCrew 4x4 in Iconic Silver Metallic

F-150 PICKUP

MAXIMUM LOADED TRAILER WEIGHT (lbs.)

Towing capability will be reduced based on trim series, option content and payload. Prior to making final vehicle selection, reference the Towing Basics information on the last page. See dealer and reference "eSourceBook" Job Aid "Spec'ing F-Series Trucks for Towing".

CONVENTIONAL TOWING

| Automatic Transmission | | SUPERCREW® | |
|-----------------------------|------------|------------------|------------------|
| Engine | Axle Ratio | 4x2 145.4" WB | 4x4 157.2" WB |
| 3.5L Hybrid V6 ¹ | 3.55 | 11,000 | |
| | | | 11,100 |
| | | 12,700 | 12,700 |
| | 3.73 | | 11,000 |
| | | | 12,300 |
| | | | 12,300 |

5TH-WHEEL/GOOSENECK TOWING

| Automatic Transmission | | SUPERCREW | |
|-----------------------------|------------|------------------|------------------|
| Engine | Axle Ratio | 4x2 145.4" WB | 4x4 157.2" WB |
| 3.5L Hybrid V6 ¹ | 3.55 | 10,200 | |
| | | | 10,400 |
| | | 10,200 | 10,400 |
| | 3.73 | | 8,500 |
| | | | 8,500 |
| | | | 8,300 |

1. Do not exceed a trailer weight of 7,000 lbs. with only the Class IV hitch (53B), without the Trailer Tow Package (53A). 2. Requires Max Trailer Tow Package (53C).

Notes: • Calculated with SAE J2807[®] method.

- Do not exceed trailer weight of 5,000 lbs. when towing with bumper only.
- Combined weight of vehicle and trailer cannot exceed listed GCWR.
- Do not exceed the Maximum Loaded Trailer Weight listed.
- Trailer tongue load weight should be 10% of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer tongue load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue load weight and weight of passengers and cargo cannot cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.